

## SAFETY DATA SHEET

---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name LEONA™  
 1200, 1200S, 1300, 1300S, 1300F, 1302S, 1400, 1402S, 1402SH, 1402F,  
 1422S, 1500, 1500Y, 1502, 1502S, 1700, 1700S, 1702, 4100, 4400, 9400S,  
 NY612, NY610

SDS No. LE-W001-10

Company Name ASAHI KASEI CORPORATION

Address 1-105 Kanda Jinbo-cho, Chiyoda-ku, Tokyo 101-8101 Japan

Contact Telephone Number

ASAHI KASEI CORPORATION(**JAPAN**)  
 Leona Plastics Sales & Marketing Dept.  
 Phone +81-3-3296-3387 , Fax +81-3-3296-3472  
 Automotive Materials Sales & Marketing Dept.  
 Phone +81-52-212-2133 , Fax +81-52-212-2229

ASAHI KASEI PLASTICS **NORTH AMERICA**, INC.  
 Phone +1-517-223-0000 , Fax +1-517-223-5620

ASAHI KASEI **EUROPE** GmbH  
 Phone +49-211-88-22-030, Fax +49-211-88-22-0333

ASAHI KASEI PLASTICS **SINGAPORE** PTE LTD  
 Phone +65-6324-3001 , Fax +65-6324-3808

ASAHI KASEI PLASTICS (**THAILAND**) CO., LTD.  
 Phone +66-35-350-720 , Fax +66-35-350-716

ASAHI KASEI PLASTICS (**SHANGHAI**) CO., LTD.  
 Phone +86-21-6391-5252 , Fax +86-21-6391-5886

ASAHI KASEI PLASTICS (**HONG KONG**) CO., LTD.  
 Phone +852-2151-4000 , Fax +852-2116-4300

ASAHI KASEI PLASTICS (**GUANGZHOU**) CO., LTD.  
 Phone +86-20-8527-1616 , Fax +86-20-8527-1700

Emergency Telephone Number

USA CHEMTREC  
 United States : (800)424-9300 24hours Everyday  
 International : +1-703-527-3887(Collect) 24hours Everyday

EU BIG v.z.w  
 Phone +32-1-458-4545 , Fax +32-1-458-3516  
 Technische Schoolstraat 43A B-2440 Geel, Belgium

Others Leona Plastics Technical Dept.  
 Phone +81-44-271-2561, Fax +81-44-271-2166  
 Business time : 9:00~18:00 on weekday

Recommended use and restriction on use

Recommended use Plastic ingredient for home electronics, electronic materials, automo-  
 tive materials, industrial materials.

## SAFETY DATA SHEET

**Restriction on use** Please do not use our product LEONA for the following use.  
 Medical containers/ packaging/ equipment/ parts of in-vivo, or which contact with mucosa, body fluid, blood, chemical solution.  
 Equipments, parts which contact with food containers/ packaging / equipment/ parts and drinking water.  
 Toys which contacts with mouth, drinking water etc.

### 2. HAZARDS IDENTIFICATION

**[GHS-Classification]**

Health Hazards                      Cannot be classified  
 Environmental Hazards            Cannot be classified

**[GHS label element]**

Pictogram or symbol            -  
 Signal word                        -  
 Hazard statements               -  
 Special Hazard                    Gas is generated in melted condition.

**[Precautionary statements]**

**Safety measures** Do not handle until all safety precautions have been read, understood and precautionary measures are taken.  
 Do not eat, drink or smoke when using this product.  
 Wear protective gloves, eye-protection if necessary. Take burn prevention measures especially when handling melted resin.  
 Install effective local exhaust in extrusion press because gas is generated.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Product Name

LEONA™ 1200, 1200S, 1300, 1300S, 1300F, 1302S, 1400, 1402S, 1402F, 1422S, 1500, 1500Y, 1502, 1502S, 1700, 1700S, 1702

Chemical name or generic name

Polyhexamethylene adipamide (Polyamide66) resin composition  
 Mixture of polyamide resin and additives (Stabilizer, Filler etc.)

Components, Contents, CAS number and EINECS number

Product Name	Components	Contents [wt%]	CAS No.	EINECS No.
1200, 1200S, 1300, 1300S, 1300F, 1302S, 1400, 1402S, 1402F, 1422S, 1500, 1500Y, 1502, 1502S, 1700, 1700S, 1702	Polyamide66	95-100	32131-17-2	N/A
	Other additives	0-5	confidential	confidential
	Total:	100wt%		

## SAFETY DATA SHEET

Other additives might contain colorant following.

Components		Contents [wt%] <sup>*)</sup>	CAS No.	EINECS No.
Other additives (All of the above grade)	Colorant	0-5	confidential	confidential
	(Carbon black)	(0-3)	1333-86-4	215-609-9
	(Iron oxide)	(0-5)	1309-37-1 etc.	215-168-2 etc.
	(Titanium dioxide)	(0-5)	13463-67-7	236-675-5
	(Silica)	(0-1)	confidential	confidential
	(Copper complex)	(0-1)	confidential	confidential
	(Complex of metal oxides)	(0-5)	confidential	confidential
	(Other colorant)	(0-5)	confidential	confidential
Other additives		0-5	confidential	confidential
Total:		0-5		

\*) The number in parentheses is included in the content of the colorant.

Product Name

LEONA™ 1402SH, 9400S

Chemical name or generic name

Polyhexamethylene adipamide and Poly-ε-caprolactam copolymer (Polyamide66/6) resin composition

Mixture of polyamide resin and additives (Stabilizer, Filler etc.)

Components, Contents, CAS number and EINECS number

Product Name	Components	Contents [wt%]	CAS No.	EINECS No.
1402SH, 9400S	Polyamide66/6	95-100	24993-04-2	N/A
	Other additives	0-5	confidential	confidential
Total:		100wt%		

Other additives might contain colorant following.

Components		Contents [wt%] <sup>*)</sup>	CAS No.	EINECS No.
Other additives (All of the above grade)	Colorant	0-5	confidential	confidential
	(Carbon black)	(0-3)	1333-86-4	215-609-9
	(Iron oxide)	(0-5)	1309-37-1 etc.	215-168-2 etc.
	(Titanium dioxide)	(0-5)	13463-67-7	236-675-5
	(Silica)	(0-1)	confidential	confidential
	(Copper complex)	(0-1)	confidential	confidential
	(Complex of metal oxides)	(0-5)	confidential	confidential
	(Other colorant)	(0-5)	confidential	confidential
Other additives		0-5	confidential	confidential

## SAFETY DATA SHEET

Total: 0-5

\*) The number in parentheses is included in the content of the colorant.

**Product Name**

LEONA™ 4100, 4400, NY612

**Chemical name or generic name**

Polyhexamethylene dodecanamide (Polyamide612) resin composition  
 Mixture of polyamide resin and additives (Stabilizer, Filler etc.)

**Components, Contents, CAS number and EINECS number**

Product Name	Components	Contents [wt%]	CAS No.	EINECS No.
4100, 4400, NY612	Polyamide612	95-100	26098-55-5	N/A
	Other additives	0-5	confidential	confidential
Total:		100wt%		

Other additives might contain colorant following.

Components		Contents [wt%] <sup>*)</sup>	CAS No.	EINECS No.
(All of the above grade)	Colorant	0-5	confidential	confidential
	(Carbon black)	(0-3)	1333-86-4	215-609-9
	(Iron oxide)	(0-5)	1309-37-1 etc.	215-168-2 etc.
	(Titanium dioxide)	(0-5)	13463-67-7	236-675-5
	(Silica)	(0-1)	confidential	confidential
	(Copper complex)	(0-1)	confidential	confidential
	(Complex of metal oxides)	(0-5)	confidential	confidential
	(Other colorant)	(0-5)	confidential	confidential
Other additives		0-5	confidential	confidential
Total:		0-5		

\*) The number in parentheses is included in the content of the colorant.

**Product Name**

LEONA™ NY610

**Chemical name or generic name**

Polyhexamethylene sebacamide (Polyamide610) resin composition  
 Mixture of polyamide resin and additives (Stabilizer, Filler etc.)

**Components, Contents, CAS number and EINECS number**

Product Name	Components	Contents [wt%]	CAS No.	EINECS No.
NY610	Polyamide610	95-100	9011-52-3	N/A
	Other additives	0-5	confidential	confidential

## SAFETY DATA SHEET

Total: 100wt%

Other additives might contain colorant following.

Components	Contents [wt%] <sup>*)</sup>	CAS No.	EINECS No.
Other additives (All of the above grade)	Colorant	0-5	confidential
	(Carbon black)	(0-3)	1333-86-4
	(Iron oxide)	(0-5)	1309-37-1 etc.
	(Titanium dioxide)	(0-5)	215-168-2 etc.
	(Silica)	(0-5)	13463-67-7
	(Copper complex)	(0-1)	236-675-5
	(Complex of metal oxides)	(0-1)	confidential
	(Other colorant)	(0-1)	confidential
	Other additives	(0-5)	confidential
	Total:	0-5	confidential

\*) The number in parentheses is included in the content of the colorant.

All of ingredients are listed on TSCA, EINECS(ELINCS), ENCS(JPN), ISHL(JPN), and IECSC(CHN) inventories.

These ingredients are corresponding to the REACH regulations.

These products do not contain Substances of Very High Concern(SVHC) concentration above 0.1wt%

#### 4. FIRST AID MEASURES

##### Swallowed

If swallowed accidentally, vomit immediately and get medical attention/advice if any abnormality occurs.

##### Eyes

Do not rub if in eyes, wash with plenty of water. Remove contact lenses immediately. If abnormality is observed get medical attention and advice.

##### Skin

Do not peel off melted material; cool down affected area with plenty of water for more than 30 minutes. Then get medical attention.

##### Inhaled

If you feel unwell, move away from the working place immediately to well-ventilated area. Get medical advice if necessary.

##### Protection who gives the first aid

Those who suffer from any abnormality should get medical attention.

## SAFETY DATA SHEET

**WARNING :Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.**

For processing fume inhalation irritation leave contaminated area and breathe fresh air. If coughing, difficult breathing or any other symptoms develop, seek medical attention at once, even if symptoms develop at a later time.

For skin contacts with condensate, immediately wash thoroughly with soap and water. If irritation develops, seek medical attention.

### 5. FIRE-FIGHTING MEASURES

Extinguisher

Pouring water, spraying water and other extinguisher can be used.

Specific hazards

Strong heat, black fume and gases such as CO<sub>2</sub>, CO, slight amount of HCN, NH<sub>3</sub> may be generated on fire.

Specific fire fighting method

Use the same fire fighting method as the general fire. Fight fire from the safe distance.

Protection of fire fighter

Wear fire retardant clothing and respiratory equipment when fighting fire. Work from the windward.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Clean up the floor immediately because it may be slippery if pellet or powder remains.

Environmental precautions

Collect all leakage on the water surface such as drain system considering adverse effect to avian species and fish.

Methods for recovery, neutralization, containment and cleaning up.

Sweep up or clean with vacuum cleaner, collect and dispose of.

Prevention of secondary disaster

See "13. DISPOSAL CONSIDERATION"

### 7. HANDLING AND STORAGE

Handling

Engineering measures

Wear eye protection, heat-resistant gloves, long-sleeved work clothing for burn prevention when handling melted resin. Avoid breathing gases generated from the melted resin.

Local exhaust, total ventilation

Use effective local exhaust at the generating point of gases because gasses are generated when handling melted resin using extruder or injection molding machine. Perform total ventilation by ventilation fan at indoor or working area operating above procedure.

Cautions to fire

## SAFETY DATA SHEET

This resin in pellet condition is flame-retardant resin component and does not ignite or explode at room temperature. However gases may be generated if fire occurs in neighborhood and fire fighting activity may become difficult. Therefore keep working area neat and tidy, do not use fire.

- (1) Do not use heater with open flame. (stove, open fire, etc)
- (2) Do not carry match, lighter. No smoking.
- (3) Ground facilities and equipments (extruder, molding machine, air-conveying line, bag filters, etc) in order to prevent static discharge.
- (4) Use safe non-sparking tools.
- (5) Avoid generation or approach of any other ignition sources.

### Precautions for safe handling

- (1) Do not eat or drink when using this product.
- (2) If leaked on the floor, remove and keep cleaned up. If leakage is left the floor becomes slippery and may cause a fall.
- (3) Determine and keep proper working process.

### Storage

Store at the place where fulfills below storage conditions.

- (1) Protect from direct sunlight.
- (2) Protect from high temperature and humidity.
- (3) Store and keep away from ignition source.
- (4) Take precautionary measures against static discharge.

### Safe containers and packaging material

Containers and packaging materials should fulfill storage conditions.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Facility measures

See "7. HANDLING AND STORAGE" for facility measures.

### Administrative level, allowable limit

Gases are generated from melted resin but administrative level and allowable limit are not established.

### Dust

Allowable limit for this resin is not established in ACGIH. However below values are applicable for dust.

<Airborne Exposure Limit (reference 1,2)>

[OSHA PEL]

15 mg/m<sup>3</sup> (Total dust)

5 mg/m<sup>3</sup> (Respirable fraction)

[ACGIH : TLV-TWA(2015)]

Particles (insoluble or poorly soluble) Not Otherwise Specified (PNOS)

10 mg/m<sup>3</sup> (Inhalable particulate)

3 mg/m<sup>3</sup> (Respirable particulate)

### Protective equipment

Respiratory protection

## SAFETY DATA SHEET

Wear gas mask for organic gas when working in a place where generated gas or fume may be breathed. Wear dust control mask when dust is caused by the works such as machinery processing of resin product, sanding, removing resing powder from bag filter, cleaning of sieving machine.

### Hand protection

It is recommended to wear hand protection if necesary. Especially when handling melted resin, wear heat-resistant gloves for burn prevention.

### Eye protection

It is recommended to wear side-shielded eye protection made with resin, resin goggles.

### Skin and body protection

Wear long-sleeved clothing when handling melted resin for burn prevention.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Pellet  
 Physical state : Solid  
 Odor : Slight specific odor  
 pH : Not applicable

### Melting point

Product name	1200, 1200S, 1300, 1300S, 1300F, 1302S, 1400, 1402S, 1402F, 1422S, 1500, 1500Y, 1502, 1502S, 1700, 1700S, 1702	1402SH, 9400S	4100, 4400, NY612, NY610
Melting point	255-270 °C (491-518 °F)	215-265 °C (419-509 °F)	200-240 °C (392-464 °F)

Decomposition point : Over 330 °C (Over 626 °F)  
 Ignition point : Over 400 °C (Over 752 °F)  
 Flash point : Over 400 °C (Over 752 °F)  
 Explosion limit : No data  
   Upper / lower : Precautionary measures for static discharge are necessary if handled as powder  
 Specific gravity : 1.1- 1.2  
 Solubility  
   Water : Insoluble  
   Other solvent : Soluble in inorganic acid (formic acid, sulfuric acid etc.)  
 Octanol / water partition coefficient : No data

## 10. STABILITY AND REACTIVITY

Stability : Stable at room temperature as far as stored protected from direct sunlight, away from fire or heat source.  
 Reactivity : No reactivity.  
 Conditions to avoid : Direct sunlight, fire, heat source and generation of its dust.

## SAFETY DATA SHEET

Materials to avoid : Not specific.

Hazardous decomposition products :

Black fume, gases such as CO<sub>2</sub>, CO, slight amount of HCN, NH<sub>3</sub> may be generated in combustion.

### 11. TOXICOLOGICAL INFORMATION

These products might contain Carbon black(≤ 3wt%), Iron oxide(≤ 5wt%), Titanium dioxide(≤5wt%), and Complex of metal oxides(≤ 5wt%).

GHS classification is shown in the table as below. This toxicological classification is based on reference 3, 4, 5, and 6.

	Resin Additives	Carbon black(*1)	Iron oxide	Titanium dioxide	Complex of metal oxides(*3)	Classification of the products
Content	≥ 95wt%	≤ 3wt%	≤ 5wt%	≤ 5wt%	≤ 5wt%	
Skin Corrosion/Irritation	Cannot be classified	Cannot be classified	Category 2	Not classified	Cannot be classified	Cannot be classified(1)
Serious Eye Damage/Irritation	Cannot be classified	Cannot be classified	Category 1	Category 2B	Cannot be classified	Cannot be classified(2)
Carcinogenicity	Cannot be classified	Cannot be classified (*2)	Not classified	Category 2	Cannot be classified	Cannot be classified(3)
Specific Target Organ Systematic Toxicity (Single Exposure)	Cannot be classified	Cannot be classified	Category 3 (Respiratory tract irritation)	Cannot be classified	Cannot be classified	Cannot be classified(3)
Specific Target Organ Systematic Toxicity ( Repeated Exposure )	Cannot be classified	Cannot be classified	Category 1 (Respiratory system)	Cannot be classified	Cannot be classified	Cannot be classified(3)

\*1) See reference 4

\*2) In the report (reference 5), the toxicological status of carbon black is specified as “not applicable”.

\*3) See reference 6

#### Notes

(1) Iron oxide exists in sold pellet, therefore it is not likely to come in contact to skin. Therefore, Classification of the products would be “Cannot be classified”..

(2) Iron oxide and Titanium dioxide exist in sold pellet, therefore it is not likely to come in contact with eyes as dust, mist, gas and vapor.

Therefore, Classification of the products would be “Cannot be classified”.

(3) Iron oxide and Titanium dioxide exist in sold pellet, therefore it cannot be drifted to atmosphere like dust, mist, gas and vapor.

Therefore, Classification of the products would be “Cannot be classified”.

**SAFETY DATA SHEET**

**12. ECOLOGICAL INFORMATION**

These products might contain Carbon black(≤ 3wt%), Iron oxide(≤ 5wt%), Titanium dioxide(≤ 5wt%), and Complex of metal oxides(≤ 5wt%).

GHS classification is shown in the table as below. This toxicological classification is based on reference 3, 4, 5, and 6.

	Resin Additives	Carbon black(*1)	Iron oxide	Titanium dioxide	Complex of metal oxides(*2)	Classification of the products
Content	≥ 95wt%	≤ 3wt%	≤ 5wt%	≤ 5wt%	≤ 5wt%	
Hazardous to the aquatic environment ( Acute Hazard )	Cannot be classified	Not classified	Cannot be classified	Cannot be classified	Cannot be classified	Cannot be classified
Hazardous to the aquatic environment ( Chronic Hazard )	Cannot be classified	Cannot be classified				

\*1) See reference 4

\*2) See reference 6

Notes

Classification of the products would be “Cannot be classified” based on GHS Classification criteria for mixture.

**13. DISPOSAL CONSIDERATIONS**

Dispose of according to regulation and standard of regional government.

Avoid direct release of waste containing this product (effluent, solid and washing water) to the river or landfill. In case of incineration treat by the method in accordance with relevant laws such as Air Pollution Control Law using the incinerator. Remove all the residues before disposal of the container (paper bag, drum, flexible container) of this product after use, dispose of in accordance with relevant laws and do not re-use for other usage.

**14. TRANSPORT INFORMATION**

International regulations

IMDG : Not Restricted  
 ICAO-TI/ IATA-DGR : Not Restricted  
 UN Classification : Not Restricted  
 UN Number : Not Restricted  
 Domestic regulations : Not Restricted  
 Marine pollutant : Not Restricted

Special safety precautions and conditions during transport :

**SAFETY DATA SHEET**

Do not handle roughly and keep dry not to break packaging bag. If the bag is broken and pellet is spilt, pay attention not to fall by slippery floor. If transported by air-conveying line take prevention measures against static discharge.

**15. REGULATORY INFORMATION****USA****OSHA :**

These products are not hazardous as defined by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**TSCA :**

All ingredients are on the TSCA inventory.

40 CFR 799 Subpart B,C :	Not Applicable
40 CFR 721 Subpart E :	Not Applicable
40 CFR 707 Subpart D :	Not Applicable
40 CFR 747,749,761,762,763,766 :	Not Applicable
40 CFR 712(d),(e) :	Not Applicable

**CERCLA/SUPERFUND (40 CFR 117,302) :**

These products contain no Reportable Quantity (RQ) Substances.

**SARA Hazard Category :**

These products have been reviewed according to the EPA Hazard Categories promulgated under SECTION 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the Following categories: Not to have met any hazard category.

**SARA 313 Information :**

These products contain no substance subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**U.S. State Regulations :**

These products might be included Carbon black, Iron oxide, and Titanium dioxide. These ingredients might be governed by various state regulations in U.S.

\*Please use these products after confirming the state regulations.

**EU**

(EC) 1272/2008 (CLP) Annex VI Table 3.1 :	Not Applicable
(EC) 1272/2008 (CLP) Annex VI Table 3.2 :	Not Applicable
(EC) 1272/2008 (CLP) :	Not Applicable
REACH Annex XIV :	Not Applicable
REACH Annex XVII :	

The products in some colors may contain a small amount of nickel compounds as the complex of metal oxides. In this case, the maximum content is 5wt%.

SVHC (REACH) :	Does not contain more than 0.1wt%.
ELV (2011/37/EU) :	Does not contain more than limit value.
RoHS (2011/65/EU) :	Does not contain more than limit value.

**China**

**SAFETY DATA SHEET**

Limited toxic chemical substances for export : Not Applicable  
 Prohibited cargo list for import and export : Not Applicable  
 List of Dangerous Goods : Those products don't contain the dangerous goods.  
 List of Hazardous Chemicals : Those products don't contain the hazardous chemicals.  
 General rule for classification and hazard communication of Chemicals. (GB.13690) :  
 Not Applicable

**Korea**

Prohibited or regulated toxic substances : Not Applicable  
 Toxic / Observed substances :  
 Those products don't contain the toxic or observed substances.

**Taiwan**

Dangerous and Harmful Materials :

These products might contain the dangerous and harmful materials.

Material name	CAS No.	Maximum content
Carbon black	1333-86-4	3wt%
Potassium iodide	7681-11-0	1wt%
C.I. pigment blue 28	1345-16-0	7wt%
Pigment Yellow 150	68511-62-6	7wt%

Toxic substances : Those products don't contain the toxic substances.

**16. OTHER INFORMATION**

These products are used only for raw material of LEONA compound.

Use is prohibited to other usages.

Refer to "LEONA Technical information " for additional guidance and information

**NOTE:**

The information furnished in this Safety Data Sheet is accurate to the best knowledge of ASAHI KASEI CORPORATION ( "Asahi" ) as of the date of its publication.

This SDS is not intended to create any liability of any kind on the part of Asahi.

In no event will Asahi be responsible for any death, injury or damage of any nature resulting from the use of, reliance upon, or misuse of the SDS or material to which it refers.

The data on this sheet relates only to the specific material designated herein.

No re-presentations or warranties, whether express or implied, of merchantability, fitness for particular purpose, or any other nature, are made hereunder.

This SDS is not intended as a recommendation for uses that infringe valid patents or extend licenses under valid patents.

This SDS is furnished under the express condition that all persons receiving it will make their own determination as to its suitability for their purpose prior to use.

Responsibility for compliance with applicable national or local regulations concerning dissemination of the SDS and sale and use of the material to which it refers rests solely upon the purchaser. For more information, please contact Asahi at the address and telephone number listed on this sheet.

---

**SAFETY DATA SHEET**

---

---

**Reference**

- 1) ACGIH, "Guide to Occupational Exposure Value", (2015)
- 2) ACGIH, "TLVs, and BEIs Based on the Documentation of the Threshold Values for Chemical Substances and Physical Agents & Biological Exposure Indices", (2015)
- 3) Incorporated Administration Agency National Institute of Technology and Education HP, "Material List of GHS Classification", <http://www.safe.nite.go.jp/ghs/list.html>
- 4) Hazard information obtained from the supplier of carbon black
- 5) Japan Carbon Black Association, "The safety of carbon black as nano-materials", (2011)
- 6) Japan Complex Inorganic Colored Pigment Association, "Safety of CICP", <http://www.kaseikyo.jp/jcicpa/E-anzensei.html>